

EURO PLUS - EMF 120

12V-120AH - AGM MONOBLOCK VRLA BATTERY

Applications:


- UPS
- Data Centers
- Emergency Lighting
- Security Systems
- Medical Instruments

Features:

- Suitable for High Rate Discharge
- Self Regulating pressure valve
- Flame retardant ABS/PP case
- Product Performance Complies with JIS 8702 C
- Design life 8 Years

Cells Per Unit	6
Voltage Per Unit	12
Capacity	120Ah @ C ₂₀ upto 1.75ECV @27°C
Weight	35 Kgs
Maximum Discharge Current(1 min 1.60 ECV)	360AMP
Operating Temperature Range	-5°C~+40°C
Nominal Operating Temperature	27°C
Float Charging Voltage	13.5 to 13.8 V
Recommended Maximum Charging Current Limit	30.0 AMP
Equalization and Cycle Service	14.4 to 15 V
Self Discharge	Batteries can be stored for more than 6 months @ 27°C Please charge batteries before using. For higher temperatures the time interval will be shorter
Construction	Plate Type: Flat Pasted Seperator: AGM Electrolyte: Immobilised H ₂ SO ₄
Terminal	M8
Container & Cover Material	PPFR

Dimensions :	Length ± 5 mm	Width ± 5 mm	Height ± 5 mm
Battery	408	171	240


Constant Current Discharge Characteristics : (Amps @ 27°C)

FV	5MIN	10MIN	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	6HR	7HR	8HR	9HR	10HR	12HR	20HR
1.60V	356.5	260.5	205.3	117.6	72.5	40.6	30.0	24.1	20.6	17.7	15.7	14.1	12.9	12.0	10.1	6.3
1.65V	337.4	247.6	193.0	114.0	71.7	39.8	29.1	23.6	20.3	17.5	15.4	13.9	12.8	11.8	9.9	6.3
1.70V	323.8	234.5	186.8	109.2	70.6	39.2	28.6	23.2	19.9	17.2	15.3	13.8	12.7	11.8	9.9	6.2
1.75V	299.3	221.6	181.8	106.4	69.7	38.4	27.9	22.7	19.6	16.9	14.9	13.5	12.3	11.4	9.7	6.1
1.80V	274.8	201.4	164.4	101.7	66.7	37.0	27.2	22.1	19.0	16.4	14.6	13.2	12.1	11.2	9.5	6.0


Constant Power Discharge Characteristics : (Watts / Cell @ 27°C)

FV	5MIN	10MIN	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	6HR	7HR	8HR	9HR	10HR	12HR	20HR
1.60V	703.1	495.8	395.0	260.2	155.7	87.4	64.4	50.4	42.0	36.1	32.2	28.6	26.0	24.4	20.7	13.3
1.65V	652.7	456.6	358.5	232.2	143.4	81.5	60.8	47.6	39.5	34.2	30.5	27.7	25.5	23.8	20.3	13.1
1.70V	602.2	434.2	347.3	224.9	140.9	79.3	58.5	46.2	38.9	33.9	30.3	27.4	25.3	23.6	20.1	12.9
1.75V	554.6	414.6	336.1	217.6	138.7	77.9	57.7	45.7	38.4	33.3	29.7	26.8	24.7	23.0	19.6	12.6
1.80V	521.0	392.2	324.9	210.1	136.1	76.5	56.6	45.1	38.1	32.8	29.1	26.4	24.3	22.5	19.2	12.4


EURO PLUS - EMF 120
12V-120AH - AGM MONOBLOCK VRLA BATTERY

PERFORMANCE CHARACTERISTICS


Discharge Curve




Charge Curve




Ocv vs. State Of charge



Residual Capacity Vs. Storage time



Temperature Vs. Capacity Curve



Temperature Vs. design Life Curve

